



SNOW BLOWER ATTACHMENTS FOR COMPACT TRACK LOADERS



Available for Terex® Models:

PT-30
PT-50
PT-60
PT-70
PT-80
PT-100
PT-100 Forestry

- Four sizes available to match the width of each loader model.
- The loader's standard auxiliary hydraulics provide power to the direct drive of the auger and fan. Connection between the loader and attachment is via quick-connect fittings and hoses that come standard. Augers are protected by a pressure relieve valve, eliminating the need for shear pins.
- Electric controls are used to rotate the discharge chute and also to adjust deflection. Chutes are of a low-friction plastic material that helps prevent plugging of wet, heavy snow.
- Blowers include high-carbon steel cutting edges and hardened steel skid shoes.

Snow Blower Attachment Ordering Reference and Specifications

Fits	PT-30	PT-50 & PT-60	PT-80	PT-100 & PT-100 Forestry
Width of cut	53 in. (1346 mm)	73 in. (1854 mm)	73 in. (1854 mm)	85 in. (2160 mm)
Height of cut	22 in. (560 mm)	29 in. (737 mm)	36 in. (914 mm)	36 in. (914 mm)
Auger diameter	12 in. (305 mm)	16 in. (406 mm)	18 in. (457 mm)	18 in. (457 mm)
Fan diameter	16 in. (406 mm)	20 in. (508 mm)	24 in. (610 mm)	24 in. (610 mm)
Chute rotation	Hydraulic	Hydraulic, 270 degrees	Hydraulic, 270 degrees	Hydraulic, 270 degrees
Casting distance, max.	25 ft (8.7 m)	30 ft (9.1 m)	40 ft (12.2 m)	40 ft (12.2 m)
Skid shoes	Hardened, adjustable	Hardened	Hardened, adjustable	Hardened, adjustable
Shipping weight	675 lb (306 kg)	975 lb (442 kg)	1800 lb (816 kg)	1,850 lb (839 kg)
Order reference	0403-242	0403-241	0402-240	0402-239

Optional Extreme Terrain tracks with 10 percent more width and deeper, more aggressive lugs than general purpose tracks are available for the PT-50 and PT-60 models. Extreme Terrain tracks will provide additional traction and flotation in wet, soft conditions as often encountered when snow blowing.

Effective date: April 2009. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex makes no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights are reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries. Copyright © 2009 Terex Corporation.

Terex Corporation
 840 Lily Lane, Grand Rapids, MN 55744
 Tel +1 (800) 346-5954 Fax +1 (218) 327-2376
www.terex.com

